

- abrasion resistance 233
- abrasive water jet cutting 206–7
- ABAQUS 51, 54, 161
- affine deformation 30
- Airbus Industry A380 198, 200–1, 211–12
- aircraft industry 197, 240–1
 - see also* thermoset prepreg
- aluminium 190–1
 - diaphragms 270
- Amoco Fabrics 220
- amplification factor 305–9
- amplification linkages 305–9
- analytical modelling 213–15
- angle classes 153, 154
- anisotropic fibre distribution 153, 154
- ARALL (aramid aluminium laminate) 199, 200
- aramid fibres 205
- Aramis 302–3
- Aromatic Polymer Composite APC-2 261
- aspect ratio 8
- asymmetric lay-ups 181–2
- audio cones for loudspeaker systems 235
- autoclave pressure 192
- automated tape laying (ATL) machines 239
- automated tow placement (ATP) machines 239
- automotive parts
 - co-moulding 273–4
 - compression moulding simulation 161–3, 164–5, 168–9
 - hot compacted 232–4
- axial loading 2, 9–10
 - see also* tensile behaviour
- axial stresses 177–8, 179
- balanced twill weave 295, 296
- benchmarking 293–317
 - forming process and fabric properties 295–7
 - future trends 315–16
 - numerical analyses 313–15
 - test procedures and results 297–313
- bending
 - FML 208
 - modelling 216–17
 - mechanical work of 94, 96
 - ply bending 2, 12–14, 245
 - tow bending 245
 - bending energy 83
 - bending stiffness 12–13
 - glass rovings 97, 98, 100
 - woven prepreg 245
- bias extension test 8–9, 294, 295
 - constitutive modelling 41–2
 - hot-compacted polypropylene 229–30
 - thermoset prepreg 244–5, 247–8
 - see also* intra-ply shear
- biaxial tension 81–2
 - model for woven fabric 89–93
 - comparison with finite element simulation and experiment 90–3
 - outline of the algorithm 89–90, 91
 - parametric description of fabric behaviour under simultaneous shear and 96–111
 - tests 9–10
- biaxial weave model 27
- bladder moulding 271
- blank holder 267
- blank holding force (BHF) 128, 136–42
- blank (preform) shape 131
 - direct method for shape optimisation 131–4, 135
- blast resistance 203
- bonding technology 199
- bowing 183–6

- breather cloth 268
- Brent's method 123
- broken fibres 128, 253
- buckling 128–9
 - test 13–14
 - tow buckling 245–6
 - see also* wrinkles/wrinkling
- bunching 248
- carbon-epoxy prepreg 240
 - see also* thermoset prepreg
- carbon fabric TPCs 257, 258–9
- carbon UD TPCs 257, 258–9
- Carreau-WLF model 148–9
- cases, protective 233, 234
- Catia Composites Design 279
- cemented carbide/hard metal tool bits 206
- centre of force 170–1
- certification 279, 281
- chemical shrinkage 179–80
 - spring-in of curved parts 187–90
 - shrinkage after vitrification 187–8
 - shrinkage before vitrification 188–90
- circumferential stresses 179
- clamping mechanisms 299–300
- classic laminate theory (CLT) 213–14
- commingled fabrics
 - benchmarking 295–316
 - consolidation behaviour 18
 - TPCs 260
 - hot stamping 267–8
- co-moulding 273–4
- compaction 2, 14, 19
 - compaction behaviour of reinforcements 14–17
 - number of compaction cycles 16
- complex parts, distortion in 192–4
- composite/metal hybrids 197–219
 - development of 198–201
 - see also* fibre metal laminates (FML)
- composite modulus 222–3
- composites design and development 277–92
- composites data exchange 281
- composites development process 278–80
- draping and forming simulation 282–4
 - linking forming simulation to
 - component design analysis 284–91
 - accounting for material shear 288–9
 - design variables for thickness and orientation 286
 - discrete optimisation 287
 - failure analysis 289
 - initial zone sizing 284–5
 - optimisation in FEA codes 285
 - ply-based analysis 287–8
 - solid element generation 290–1
 - stochastic analysis 289–90
 - zone description 285–6
 - zone orientation 287
 - zone and ply descriptions 277–8
- compression 81–2
 - fabric behaviour under simultaneous shear and tension 111
 - glass rovings 97–9, 100
 - model of compression of woven fabric 84–9
 - outline of the algorithm 84–5
 - 2D laminates 86–8
 - 3D fabrics 88–9
 - yarns in a relaxed woven fabric 83–4
- compression moulding 1, 144
 - TPCs 264–8
 - flow moulding of GMT 264–7
 - hot stamping of commingled fabrics and aligned prepregs 266, 267–8
- compression moulding simulation 144–76
 - examples of use 161–71
 - fibre orientation simulation 164–5
 - flow simulation 161–4
 - quality control 169–71
 - stiffness and failure analysis 166–9
 - measurement of material data 172–4
 - theoretical description 145–61
 - calculation of fibre orientation 153–61
 - flow transfer simulation 145–9
 - heat transfer simulation 149–53
- COMPRO 193
- conduction 149
- conjugate gradient (CG) method 118, 121–4
- consolidation 2, 14, 181
 - consolidation behaviour of prepreg 17–19
 - effect on spring-in 191–2
 - multi-ply forming and re-consolidation simulations 70–5
- constitutive axes 52, 53
- constitutive modelling 22–45
 - continuum-based laminate modelling *see* continuum-based laminate modelling
 - continuum models 26–9
 - discrete models 23–6
 - future trends 43–4
 - multi-layered models 29
- continuous approaches to FE analysis 49–57
 - hyperelastic model 51–4
 - macromechanical model used in a commercial FE code 56–7
 - non-orthogonal constitutive models 54–6

- continuous fibre reinforcements 48, 224–5
- continuous fibres reinforced thermoplastics (CFRTP) 70–5
 - prepregs 49
 - simulation of CFRTP forming processes 71–2
- continuum-based laminate modelling 29–43
 - constitutive equation for a single layer 31–4
 - kinematics 30–4
 - multi-layer effects 34–5
 - parameter characterisation 35–43
 - bias extension 41–2
 - picture frame 36–41
 - pull-out 42–3
- continuum drape models 26–9
 - elastic models 26–7
 - multi-component models 27–9
 - viscous models 27
- continuum theory 166, 167
- control volume approach 147
- convection 149
- convergence speed 120–1, 122
- cooling stage 127
- Cooperative Research Centre for Advanced Composite Structures (CRC-ACS) 253, 254
- corner thickening/thinning 181, 191–2
- corrosion resistance 205
- cost analysis 117
- crack bridging 202–3
- crack growth
 - aluminium alloy 200, 202
 - FML 200, 202, 214–15
- crimp 60, 85, 223, 245–6
 - de-crimping 9
 - elementary crimp intervals 82–3
 - heights 82–3, 84, 89–90
 - non-crimp fabrics *see* non-crimp fabrics (NCFs)
- critical fibre concentration 155
- cross ply (CP) laminates 207
- cure, degree of 150–1
- curing, differential 181
- CURV 220, 224, 233, 234, 236
 - see also* hot compaction
- curved parts/plates 178–9
 - spring-in of 186–92, 194
- cutting 205–7, 218
- cyclic thermoplastic polyesters (CBTs) 274–5
- dampening term 156
- Darcy law 47
- dashboard 162, 164
- data exchange 281
- de-crimping 9
- defects 128–30, 131
 - see also* buckling; wrinkles/wrinkling
- deformation gradient 54
- deformation energy 172
- deformation mechanisms 1–21
 - axial loading 2, 9–10
 - compaction 2, 14–17, 19
 - consolidation 2, 14, 17–19
 - intra-ply shear 2, 3–9, 19
 - ply bending 2, 12–14
 - ply/tool and ply/ply friction 2, 10–12
 - in woven fabric prepreg 241–7
- degrees of freedom (DOFs) 29
- delamination 227–8
- density 204
- dependencies 96, 103–5, 106–7
- design points (parameter sets) 125–6
- diaphragm forming 127–8
 - thermoset prepreg 248–9
 - diaphragm materials 251
 - tooling 251–2
 - TPCs 270–1
- differencing points 150
- differential curing 181
- differential thermal contraction 177–9, 180, 181–2
- diffusion 149
- direct methods for optimisation 142
 - shape optimisation 131–4, 135
- discrete (mesoscopic) approach to FE analysis 50, 57–9
- discrete drape models 23–6
 - mapping-based schemes 23–4
 - particle-based schemes 24–5
 - truss-based schemes 25–6
- discrete layer calculation of fibre orientation 159–60
- discrete optimisation 287
- distortion 177–96
 - in flat parts 181–6, 194
 - fundamental mechanisms 177–81
 - in more complex parts 192–4
 - spring-in of curved parts 186–92, 194
- door panel 161–3, 164–5, 168–9
- double curved laminates 212–13
- double-diaphragm forming 248–9, 270–1
- doublers 212
- downhill simplex (DS) method 118–21, 122
- drape modelling 22–3, 46–7
 - constitutive modelling *see* constitutive modelling

- drape simulation 246, 282–4
 - comparison with forming simulation 284
 - see also* composites design and development
- dressed virtual humans 25
- drilling 207
- dry fabrics 1
- ductility 223, 224

- E-LFT (endless fibre reinforced long fibre thermoplastic) 274
- edge milling 206–7
- elastic energy 208
- elastic material continuum models 26–7
- elastic stress 31–2
- electrical properties 204
- elementary crimp intervals 82–3
- empirical models 16–17
- enclosed fibre angle 31
- energy-based mapping method 24
- energy method for normalisation 311–12, 313
- energy transport *see* heat transfer simulation
- equilibrium, picture frame 39
- errors 93
- ESI-QuickFORM 46
- expansion coefficients 177–9, 180
- EXPRESS 145, 161

- fabric area, normalisation by 311, 312
- fabric-based TPCs 257, 258–9, 260–1
 - co-moulding 273–4
 - hot stamping 267–8
- fabric reinforced fluid (FRF) model 30
- fabric thermoset prepreg 241–7
- fabrics, simplified dynamic equation for 60–1
- failure analysis
 - composite design and development 289
 - simulation of compression moulding 166–9
- failure factor 167–8, 170
- failure strain 201–2, 207
- fatigue
 - resistance for FML 199, 200, 202–3
 - stress intensity factors for FML 214–15
- FiberSIM 46
- fibre breakage 128, 253
- fibre bridging 202–3
- fibre distribution function 153, 154, 156, 160–1
- fibre extension (stretch) 30
 - thermoset prepreg 246, 254
- fibre interaction coefficient 156–7
- fibre metal laminates (FML) 197–219
 - development of 199–201
 - modelling 213–17, 218
 - analytical modelling of mechanical properties 213–15
 - FE modelling of FML structures 215–16
 - forming processes 216–17
 - lay-up processes 217
 - production processes 205–13, 218
 - cutting processes 205–7, 218
 - formability aspects 207–8
 - forming processes 208–11
 - lay-up techniques for FML shells 211–13
 - properties 201–5, 218
 - mechanical 201–3
 - physical 204–5
- fibre orientation
 - design variables for 286
 - distribution 128
 - reorientation 22
 - simulation and composite design 279, 280
 - simulation of compression moulding 153–61
 - examples of use 164–5
 - fibre pre-orientation 160–1
 - fibre transport 153–5
 - model for calculation of fibre rotation 155–8
 - solution of differential equation 158–9
 - thermoplastic discrete layer calculation 159–60
 - thermoset prepreg 241
- fibre volume fraction 14–17
 - gradients 181, 182–3
- fibre wrinkling, spring-in due to 190–1
- filament wound tubes 180
- finite difference method 150–1
- finite element analysis (FEA) 25–6, 46–79, 81–2, 193–4, 277–8
 - approaches to 49–50
 - bi-component model of dry fabric forming 28
 - commercial FE code 56–7
 - comparison of model of uniaxial and biaxial tension of woven fabric with 90–3
 - component design analysis and optimisation 285–91
 - composite development process 279
 - continuous approaches 49–57

- discrete approach 50, 57–9
- forming simulation 284
 - comparison with kinematic simulation 284
- mechanism and specificity of composite forming 48–9
- modelling of FML structures 215–16
- multi-ply forming and re-consolidation simulations 70–5
- multi-scale materials 48
- semi-discrete approach 59–70
- fire resistance 204–5
- fishnet model 23–4
- FIT (Fibre Impregnée de Thermoplastique) process 261
- flame treatment 233–4
- flat plates/parts 178
 - distortion 181–6, 194
 - due to asymmetric lay-ups 181–2
 - due to resin bleed and volume fraction gradients 182–3
 - due to tool-part interaction 183–6
- flattening coefficient 99, 100, 111
- flow conductivity 146–7
- flow moulding 264–7
- flow simulation 145–9
 - examples of use 161–4
 - isothermal 146–8
 - non-isothermal 148–9
- Fokker 199
- Folgar-Tucker fibre orientation model 155–7
- footwear, safety 235
- formability 207–8
- forming boxes 251–2
- forming limit diagram (curve) 129–30, 131, 132, 133, 216
- four-node finite element 65–7
- frame angle 37–8, 301
- frame length 310, 311
- friction 2, 10–12, 56–7
 - between glass rovings and steel 99, 100
 - moment 94, 95
 - stress gradients due to frictional effects before gelation 185–6
- fully constituted TPCs *see* unidirectional (UD) TPCs
- gelation 188, 190
- generators (fibre paths) 282–3
- geodesic generators 283
- geometric model 23–4
- GLARE laminates 200–1, 202, 204, 214
- glass fabric TPCs 257, 258–9
- glass fibre-based GLARE 200
- glass fibre-reinforced polymers 39–41, 224–5
- glass mat thermoplastic (GMT) 1, 144
 - forming trials for self-reinforced polypropylene using a commercial GMT production line 230–1
- TPCs 257, 258–9
 - co-moulding 273–4
 - flow moulding 264–7
- glass rovings, properties of 97–100
- glass transition temperature 181–2
- glass UD TPCs 257, 258–9
- global failure criterion 167
- global ply modelling 279, 280
- GMTText 274
- golden section method 123
- gradient techniques 285
- Green-Naghdi approach 51, 52
- Halpin-Tsai model 166
- hand lay-up 240–1
- heat sources 250–1
- heat transfer simulation 149–53
 - energy transport after filling stage 149–51
 - energy transport after part ejection 152–3
 - energy transport during filling stage 149
 - four stress layers 151–2
- Hele-Shaw flow model 145, 146
- helper points 150, 152–3
- hemispherical forming
 - matched hemispherical mould experiments 226–9
 - optimisation of process parameters 136–40
 - unbalanced fabric 67–70
- high temperature polymer diaphragms 251, 270
- homogenisation 51
- honeycomb structure 199
- Hong Kong University of Science and Technology (HKUST) 294, 297–313, 314
- hoop stresses 177, 178
- hot compaction 220–38
 - commercial exploitation 224–5
 - commercial products 232–5
 - future developments 235–6
 - postforming studies 225–32
 - forming trials using a commercial GMT production line 230–1

- picture frame and bias extension tests 229–30
 - tensile tests and matched hemispherical mould experiments 226–9
 - thermoforming strategies 232
 - process 220–4
- hot compaction temperature 222
- hot stamping process 266, 267–8, 295–7
- hybrid drape algorithm 25
- hybrid materials 197
 - development of composite/metal hybrids 198–201
 - FML *see* fibre metal laminates
- hydrostatic stress 32
- hyperelastic model for fibrous materials 51–4, 55
- impact resistance 203, 233
- implicit method 158–9
- in-plane deformations
 - FML 207
 - modelling 216
 - semi-discrete approach and in-plane shear 62–5
 - see also* intra-ply shear
- inclined plane method 10–11
- indirect (iterative) optimisation methods 134–42
- initial zone sizing 284–5
- injection 48
- input data 111–12
- interacting particle model 24–5
- interaction between fibres 155–7
- interface traction 35, 42–3
- interior elementary work 65–7
- internal stresses *see* residual stresses
- interply shear (interply slip) 71
 - woven fabric prepreg 241–3
- intertow slip 246
- intra-ply shear 2, 3–9, 19, 207
 - benchmarking 294, 297–316
 - bias extension test *see* bias extension test
 - constitutive modelling 36–42
 - picture frame test *see* picture frame test
 - thermoset prepreg 243–4, 247–8
- intra-ply tensile loading 2, 9–10
- Invar 190
- isothermal bladder moulding 271
- isothermal diaphragm forming 270
- isothermal flow simulation 146–8
- isothermal forming 262, 263
- isothermal vacuum forming 268–9
- isotropic fibre distribution 153, 154
- isotropic polypropylene sheet 224–5
- iterative optimisation method 134–42
- Jaumann approach 51
- Jeffrey model for fibre orientation 155
- Katholieke Universiteit Leuven (KUL) (Belgium) 294, 297–313, 314, 315
- Kawabata Evaluation System for Fabrics (KES-F) 3, 36
- kinematical models 46
 - continuum-based laminate modelling 30–4
 - discrete model 23–4
 - draping simulation 282–4
 - compared with finite element forming simulation 284
- Kriging method 125–6
- Laboratoire de Mécanique des Systèmes et des Procédés (LMSP) (France) 294, 297–313, 314
- LAM option 285–6
- laminates 178
 - compression of 86–8
 - zone and ply descriptions 277–8
- laser jet cutting 206–7
- lay-up processes
 - FML 211–13, 218
 - modelling 217
 - hand lay-up 240–1
- Lie derivative 54, 55
- linkages, amplification 305–9
- liquid composite moulding (LCM)
 - processes 49
- locking 60, 102, 107, 180, 245
- locking angle 4–5, 8, 107, 129, 230, 282
 - benchmarking 310, 314–15
- long discontinuous fibre prepreg 254
- long fibre thermoplastic (LFT) 273–4
- looseness factor 100–1
- luggage, protective 234
- macromechanical models
 - compression moulding simulation 166, 167–8
 - used in a commercial FE code 56–7
- macroscopic scale 48
- magnetic properties 204
- mandrels 251–2
- manufacture, composite design and 279–80, 281
- mapping approaches 23

- drape modelling 23–4
 - mapping function 133–4
 - masses and springs 58, 59
- matched mould processes 18
 - matched hemispherical mould experiments 226–9
- material data measurement 172–4
- material property sets 289
- materials characterisation 1–21
 - axial loading 2, 9–10
 - benchmarking *see* benchmarking
 - compaction 2, 14–17, 19
 - consolidation 2, 14, 17–19
 - constitutive modelling 35–43
 - intra-ply shear 2, 3–9, 19
 - ply bending 2, 12–14
 - ply/tool and ply/ply friction 2, 10–12
- matrix phase 221–3
- mechanical conditioning of samples 301, 309–10, 313, 315
- mechanical fastening 207
- mechanical modelling 23
- mechanical properties
 - FML 201–3
 - analytical modelling 213–15
 - TPCs 258–9
 - see also under individual properties*
- mechanical simulation of compression moulding 166–9, 170
- mechanical work of shear deformation 93–6
- melt impregnation 259
- melted and recrystallised phase 221–2, 227–8
- melting peaks 221–2, 227–8
- mesoscopic (discrete) approach to finite element analysis 50, 57–9
- mesoscopic scale 48
- metal matrix composites (MMCs) 197–8
- metal sheet 129, 130
 - optimisation 140–2
- metal volume fraction (MVF) approach 214
- micromechanical models 43, 166–7
- microscopic scale 48
- minimum bend radius 208
- minimum energy, principle of 80–1, 84, 90
- moisture uptake 181, 182
- molecular weight 224
- mould filling 47
- MSC.Nastran 279, 287–8
 - PCOMP card 285, 286
- Mullins effect 251
- multi-component continuum models 27–9
- multi-layered composites 24
 - continuum-based laminate modelling 34–5
 - drape models 29
- multi-ply forming 70–5
 - shell element with pinching 72–4
 - simulation of CFRTP forming processes 71–2
 - simulation of forming and re-consolidation stage of a Z profile 74–5
- multi-scale materials 48
- natural element method (NEM) 46
- nesting 86–8
- Newton-Raphson (NR) method 134
- Newtonian flow 145, 146–7
- nodal interior load 65–7
- non-crimp fabrics (NCFs) 5, 6, 57
 - meso-mechanical model 59
 - optimisation of process parameters for NCF with tricot stitch 136–40
- non-isothermal diaphragm forming 270–1
- non-isothermal flow simulation 148–9
- non-isothermal forming 262–4
- non-isothermal vacuum forming 269–70
- non-Newtonian flow 145
- non-orthogonal constitutive models 54–6
- normalisation 9
 - benchmarking studies 300, 310–13
- NSF Composite Sheet Forming Workshop 293
- numerical forming investigation 313–15
- nylon twill 67–70
- objective derivatives 51–4, 55
- objective functions 118, 132–4, 135, 142
 - in composite forming 127–31
 - sheet metal and optimisation of BHF 141–2
- optical measurement of shear angle 302–3
- optical strain analysis 63, 64
- optimisation 117–43
 - component design analysis 284–91
 - composite forming 126–42
 - objective functions 127–31
 - optimisation of process parameters using iterative optimisation method 134–42
 - shape optimisation using a direct method 131–4, 135
 - methods 118–24
 - using a surrogate model 124–6
- orientation *see* fibre orientation

- orientation tensors 153
- oriented fibre phase 221–2, 227–8
- out-time (age) 240–1
- over-injection moulding 273
- overlap splice 212

- PAM-FORM code 56–7
- parallel simulations 121, 124
- part ejection, heat flow after 152–3
- partially impregnated materials 17–18
- particle-based drape models 24–5
- performance analysis 117
- phenomenological models 16
- physical properties of FML 204–5
- picture frame test 3–7, 63–4
 - benchmarking 294, 297–313
 - continuum-based laminate modelling 36–41
 - equilibrium 39
 - kinematics 37–9
 - hot-compacted polypropylene 229–30
 - pre-consolidated laminates 39–41
 - types of frame 298–9
- pinching 72–4
- plain weave 295, 296
- ply bending 2, 12–14, 245
- ply descriptions 277–8
- ply details 279, 281
- ply drop-off 279
- ply lay-up 279, 281, 287, 288
- ply/ply friction 2, 10–12
- ply pull-out tests 11, 42–3
- ply/tool friction 2, 10–12, 43
- poly crystal diamond (PCD) tipped tool bits 206
- polyetherimide (PEI) 261
- polyethersulphone (PES) 261
- polyethylene 221–2, 223, 235–6
- polyethylene naphthalate (PEN) 236
- polyethylene terephthalate (PET) 222, 223, 236
- polyoxymethylene (POM) 236
- polypropylene (PP)
 - comparison of mechanical properties of PP-based materials 224–5
 - self-reinforced composites 221, 222, 223–5, 236
 - commercial products 232–5
 - postforming studies 225–32
- pores 71–2
- post yield modulus 226, 227
- powder impregnated fabrics 260–1
 - hot stamping 267–8
- preconditioning 301, 309–10, 313, 315
- preform shape *see* blank (preform) shape
- preforming 22, 240
- pre-orientation distribution factor 160–1
- prepreg 1, 239
 - consolidation behaviour 17–19
 - picture frame test 5, 7
 - thermoplastic 127–30, 131
 - thermoset *see* thermoset prepreg
- press brake bending 209
- press forming 210, 211, 249–50
- Press rheometer 172–4
- pressing force, calculated vs measured 163–4
- pressure
 - autoclave pressure 192
 - distribution and hot stamping 267–8
 - temperature-pressure-time profiles 262–3
- process parameters 127
 - optimisation 117, 131–42
 - iterative optimisation method 134–42
 - shape optimisation 131–4, 135
- projected generators 283
- Propex Fabrics 220, 224
- protective cases and luggage 233, 234
- pull-out tests 11, 42–3

- quality control 169–71
- quenching 262, 263

- radial stresses 177, 178
- random short glass fibre filled polypropylene 224–5
- rate of deformation tensor 32–3, 38
- reaction moulding 274–5
- re-consolidation 70–5
 - see also* consolidation
- reinforcement compaction 2, 14–17, 19
- relaxed state of a woven fabric, model of 82–4
- release film 268
- repeatability 309–10, 313, 315
- representative volume elements (RVEs) 25–6
- residual strength 203
- residual stresses 177–96
 - distortion in flat parts 181–6
 - distortion in more complex parts 192–4
 - FML 204, 208
 - double curved laminates 213
 - fundamental mechanisms causing 177–81
 - spring-in of curved parts 186–92
- resin bleed 181, 182–3, 191–2
- resin infusion 18, 211

- resin-poor regions 183
- resin-rich regions 181, 183
- responsive surface method (RSM) 124–5
- rhombus test *see* picture frame test
- riveted joints 215–16
- roll bending 210
- roll forming 210, 211
 - TPCs 272
- Rosenbrock functions 119–20, 121, 123, 125
- routing 206–7
- rubber press forming 249–50

- safety footwear 235
- sample preparation 300–1
- sandwich materials 197, 199
- sandwich moulding 274
- saturation 16
- scissor and slide draping mechanisms 282
- self-reinforced composites *see* hot compaction
- semi-discrete approach 59–70
 - experimental and virtual test for tensile and in-plane shear behaviour 62–5
 - four-node finite element made of woven cells 65–7
 - hemispherical forming of an unbalanced fabric 67–70
 - simplified dynamic equation for fabrics 60–1
- semi-preg materials 17–18
- shape
 - composites development process 278–9, 281
 - objective functions and shaping 127–31
 - optimisation 129–31
 - direct method 131–4, 135
 - process capabilities of thermoset prepreg 253, 254
- shear 81–2
 - composite design and development 288–9
 - in-plane shear behaviour 62–5
 - intra-ply shear *see* intra-ply shear
 - model of shear of woven fabrics 93–6
 - parametric description of fabric
 - behaviour under simultaneous shear and tension 96–111
 - comparison with experiments 105–11
 - parameterisation of the shear diagram 100–5
 - properties of glass rovings 97–100
 - shape of the shear diagrams 101–3
 - shear angle 5–7, 31, 38, 137, 138, 301–3
 - benchmarking 306, 309, 315
 - vs shear force 5–7, 39, 40–1, 309–13
 - shear couple 61, 63–4
 - shear edges 265–6
 - shear force 5–7, 217
 - benchmarking 304–5, 306–8, 309
 - normalisation 310, 311, 312, 313
 - vs shear angle 5–7, 39, 40–1, 309–13
 - shear lag analysis 189–90
 - shear modulus 103–5, 106–7
 - benchmarking study 313–15
 - shear resistance 103–5
 - shear strain interpolation 66
 - shear stress 314
 - ply/tool friction 11–12
 - shearing 206
 - sheet forming 117
 - optimisation *see* optimisation
 - sheet moulding compounds (SMCs) 1, 144
 - see also* thermoset prepreg
 - shell-based drape models 26–7
 - shell elements 290
 - with pinching 72–4
 - short fibres 48
 - shrinkage 229
 - chemical *see* chemical shrinkage
 - silicone rubber diaphragms 251, 270
 - simplex 119
 - see also* downhill simplex method
 - simplified dynamic equation 60–1
 - single curved laminates 212
 - single-diaphragm forming 248, 249
 - skin panels for aircraft structures 211–12
 - sled runner 171
 - slip factor 35, 42
 - slip law 35
 - slurry deposition (wet laying) 259
 - smooth particle hydrodynamics (SPH) 46
 - soccer shin guards 233, 234
 - solid element generation 290–1
 - solvent impregnated TPCs 261
 - splices/splicing 212, 279
 - sports protection 233, 234
 - spring back 208
 - spring-in 179, 180
 - of curved parts 186–92, 194
 - effect of consolidation 191–2
 - fibre wrinkling and tool-part interaction 190–1
 - shrinkage after vitrification 187–8
 - shrinkage before vitrification 188–90
 - thermoelastic spring-in 186–7
 - squeeze flow rheometers 172–4
 - stack forming behaviour 247

- stamp forming 127–8
 - hot stamping 266, 267–8, 295–7
 - TPCs 264–8
 - see also* compression moulding
- standardisation 36, 315
- stationary layers 159, 160
- stiffening index 16–17
- stiffness analysis 166–9
- stochastic design improvement (SDI) 289–90
- strain interpolation coefficients 66–7
- strain tensor 53
- stress gradients 184–6
- stress intensity factors 214–15
- stress layers 151–2
- stress-strain relations
 - FML 201–2
 - modelling 213–14
 - hot compacted polypropylene sheet 226, 227
 - non-orthogonal constitutive models 55–6
 - silicone rubber 251
 - woven fabric prepreg 244–5
- stress tensor 50, 53
- stretch forming 210, 211
- structural analysis 279
- suitcase shell 162, 163–4
- surface activity 233–4
- surface profile functions 86
- surrogate model 124–6

- tape prepreg 247–8
- tearing 129–30, 131
- Technical University of Delft 199–200
- temperature
 - hot compaction process
 - hot compaction temperature 222
 - melting peaks of two phases 221–2, 227–8
 - postforming studies 226–32
 - thermoset prepreg 246
- temperature-pressure-time profiles 262–3
- tensile behaviour 2, 9–10
 - fibre metal laminates 201–2
 - glass rovings 98, 99–100
 - model of uniaxial and biaxial tension of woven fabric 89–93
 - parametric description of fabric
 - behaviour under simultaneous shear and tension 96–111
 - self-reinforced polypropylene 226–9
 - semi-discrete approach 62–5
- tensile modulus 90–1, 201, 202, 257, 258–9
- tensile strength 257, 258–9
- tensile surfaces 60–1, 62, 63
- tension tensor 61
- Tensylon 236
- thermal contraction, differential 177–9, 180, 181–2
- thermal history 246
- thermoelastic spring-in 186–7
- thermoforming 127–8, 240
 - thermoforming studies of self-reinforced polymers 225–32
- thermoplastic composites (TPCs) 144, 256–76
 - basic principles of TPC forming technologies 262–4
 - discrete layer calculation of the fibre orientation 159–61
 - drape models 28
 - forming methods 264–72
 - recent developments 273–5
 - TPCs for forming 256–62
- thermoplastic prepreg 127–30, 131
- thermoset composites
 - hot compaction process *see* hot compaction process
 - see also* thermoset prepreg
- thermoset prepreg 49, 144, 239–55
 - deformation mechanisms in woven fabric prepreg 241–7
 - diaphragm forming tooling 251–2
 - forming processes 248–50
 - future trends 253–4
 - potential problems 252–3
 - practicalities of forming thermoset prepreg stacks 240–1
 - process capabilities 253, 254
 - tape prepreg 247–8
 - tooling and equipment 250–1
- thermostamping process 266, 267–8, 295–7
- thickness
 - design variables for 286
 - diversity 128
 - glass rovings 97
- three-dimensional (3D) fabric, compression of 88–9
- through-thickness contraction 188–90
- through-thickness expansion coefficients 179, 180
- tool-part interaction 180
 - distortion in complex parts 192–3
 - distortion in flat parts 183–6
 - spring-in due to 190–1
- tool/ply friction 2, 10–12, 43

- torsion, mechanical work of 94, 95, 96
total Cauchy stress 31–4
tow bending 245
tow buckling 245–6
transversal forces 89–90, 93, 94
transverse stretching 248
trellising *see* intra-ply shear
tricot stitch, NCF with 136–40
truss elements 25–6, 58
twist 178, 179
two-dimensional (2D) laminates,
 compression of 86–8
- ultimate tensile stress 201, 202
unbalanced fabric 67–70
 twill weave 295, 296
unbending of yarns, mechanical work of
 94, 96
uniaxial tension model 89–93
 comparison with finite element
 simulation and experiment 90–3
 outline of algorithm 89–90
unidirectional (UD) laminates 207
unidirectional (UD) TPCs 257, 258–9,
 261–2
 hot stamping 267–8
unit cells 25–6
University of Massachusetts Lowell
 (UML) (USA) 294, 297–313, 314,
 315
University of Twente (UT) (Netherlands)
 294, 297–313, 314
- vacuum consolidation 18
vacuum forming 268–70
vacuum infusion 16
vacuum pump/compressor 250
vacuum table 269
Vantage Polymers Ltd 220
variable layers 159–60
velocity profile 154, 159–60
vertical displacement, mechanical work of
 94, 96
virtual testing 19, 80–116
 creating input data for forming
 simulations 111–12
 mechanical model of the internal
 geometry of the relaxed state of a
 woven fabric 82–4
 model of compression of woven fabric
 84–9
- model of shear of woven fabric 93–6
model of uniaxial and biaxial tension of
 woven fabric 89–93
parametric description of fabric
 behaviour under simultaneous shear
 and tension 96–111
 comparison with experiments 105–11
 parameterisation of the shear diagram
 100–5
 properties of glass rovings 97–100
viscosity 57, 172–4, 246
viscous material continuum models 27
viscous stress 31, 32–3
viscous traction 35, 42–3
vitrification
 chemical shrinkage after 187–8
 chemical shrinkage before 188–90
volume fraction *see* fibre volume fraction
von Mises strain distribution 302–3
von Mises stresses 177–8
- wall adhesion 173, 174
wall slippage effects 172–4
warp yarns 101
weave patterns 82–3, 100
weaving density 100–1
weft yarns 101
wet laying (slurry deposition) 259
width, roving 97
WiseTex 82
woven cells 65–7
wrinkles/wrinkling 4, 22, 181, 310
 finite element analysis 68–70
 optimisation of composite forming
 128–30, 131, 138–40
 sheet metal optimisation 129, 130
 spring-in due to fibre wrinkling 190–1
 thermoset prepreg 252–3
 woven prepreg 245–6
- yield stress 201, 202
Young's modulus 90–1, 201, 202, 257,
 258–9
- Z reinforcement 71
 simulation of forming and
 re-consolidation stage 74–5
zone descriptions 277–8, 285–6, 287–8
zone lay-up 279, 281
zone orientation 287