

- ABC (alternate billing services), 617
- A-bis interface, 465
- Access attempts, 81
- Access channel, 74, 81, 261
 - CDMA, 505
 - GSM, 471
 - NA-TDMA, 491
 - separation between access and paging, 266
- Adaptive antenna array, 571
- Additional spectrum, illus., 258
- Additional spectrum management, 90
- Additional spectrum radio, 97
- ADC (American digital cellular, NA-TDMA, IS-54), 468
- ADF (average duration of fades), 22, 390
- A-interface, 465
- Air interface, 465
- Air-to-ground systems, 4
- AIN (advanced intelligent network), 617
 - mobile AIN, 624
- Alerting, 83
- Amplifier noise, 24
- AMPS, 486
- Antenna(s), 69
 - abnormal antenna configuration, 170
 - directional, 172
 - omnidirectional, 167
 - cell site, 147, 167
 - increasing height, 309
 - roof-mounted, 329
 - collinear-array case, 163
 - combiner, 241
 - channel, 241
 - fixed-tuned, 253
 - frequency-agile, 243
 - ring, 253
 - tunable, 253
 - directional, 172, 196-200, 338
 - discone, 176
 - equivalent circuit of, 157
 - Antenna(s), equivalent circuit of (Cont.):
 - regular check of, 180
 - interference reduction, 177
 - location, 174
 - mastless, 329
 - mature system configuration, 172
 - microwave: characteristics of, 376
 - back-to-back coupling, 378
 - front-to-back ratio, 377
 - sidelobe, 377
 - side-to-side coupling loss, 378
 - installation of, 379
 - minimum separation between, 179
 - at cell site, 179
 - at mobile site: horizontal, 184
 - vertical, 186
 - mobile (see Mobile antennas)
 - different antenna mountings, 334
 - glass-mounted, 183
 - mobile high-gain, 183
 - roof-mounted, 181
 - narrowbeam concept, 334
 - null-free pattern (see Patterns)
 - omnidirectional, 62, 194, 337
 - parasitic elements, 211
 - set-up channel, 174
 - space diversity, 175
 - sum patterns, synthesis of, 165-166
 - tilting, 205, 207, 208
 - umbrella-pattern, 175
- Antenna height:
 - effective, 109, 131-135, 146
 - lowering (see Lowering antenna height)
- Antenna-height gain, 132, 135
- Antenna height to antenna spacing ratio, 215
- Antenna separation requirement for:
 - diversity:
 - at cell site, 217
 - at mobile unit, 217
- Antenna site, choosing, 160

- Area-to-area prediction curves, 106
 - standard condition for, 107
- ARQ (automatic repeat request), 470
- ASE (application service element), 621
- ATM (asynchronous transfer mode), 623
 - cell, 623
 - packet-switching, 628
 - switches, 629
 - technology, 625
 - transmission, 628
- Aurora, 31
- Authentication, 481
 - CDMA, 515
 - GSM, 481
 - NA-TDMA, 500
- Automatic-repeat request (ARQ), 424, 440
- AUC (authentication center), 486
- Available noise power, 24
- Average duration of fades (ADF), 22, 390
- Average noise level, 398, 399
- Average signal strength, 395
- AXE 10 switch, 32

- Band A carriers (list of first 90 cities), 43-47
- Band B carriers (list of first 90 cities), 43-47
- Bit synchronization, 433
 - B-ISDN, 624
- Blockage, 381
 - set-up channel, 381
 - tqta, 384
 - voice channel, 383
- Blocked-Calls-Cleared, table, 35-42
- Blocking:
 - average, 275
 - handoff, 277
- Blocking probability, 10, 382
 - voice channel, 383
 - end-office trunk, 383
- Broadside-array case, 162
- BSC (base station controller), 464
- BSS (base station subsystem), 464
- BTA (basic trading area), 643
- BTS (base transceiver station), 464
- Building height effect, 419
- Building penetration, 417
- Bursts and training sequences, 465

- Call attempt, 81
- Call attempt repeats, 382
- Call congestion, 347
- Call control (CC), 468, 483
- Call dropped rate formula, 299
- Call drops, 10, 297, 349, 384
 - due to handoff, 384
 - due to loss of SAT, 384
 - relationship among, 298
- Call initialization, 26, 80
- Call initiation, 81-83
- Call processing, 80, 529
- Calls per hour per cell, 53
- Canadian cellular system, 31
- Carrier-phase tracking, 431
- Carrier recovery, 430
- Carrier-to-interference ratio, 60
- CCIS (common channel interoffice signaling), 620
- CCSS, 621
- CDF (cumulative distribution function), 17
- CDMA (code division multiple access), 503
 - design CDMA system, 607
 - direct sequence, 576
 - frequency hopping, 578
 - long code, 505
 - non-uniform cell, 608
 - radio network, 601
 - short code, 505
 - uniform cell, 603
- CDPD (cellular digital packet data), 544
- CDVCC (coded digital verification color code), 501
- Cell, uniform-coverage, 330
- Cell-site antenna, 157, 167
- Cell-site locations, selecting, 309
- Cell selection, 481
- Cell sites, 8
 - controller, 351
 - high-site versus low-site, 356
 - between highway separation, 337
 - portable, 333
 - selection locations, 299
- Cell splitting technique, 326
 - effect on, 328
 - permanent, 67, 325
 - real-time (dynamic), 327
 - size limitation, 328
- Cellular allocated frequencies, 6
- Cellular systems, 73, 463, 486, 503, 534
 - fixed, 642
 - mobile, 73, 421
 - non cellular system, 544
 - outside United States, 29-33
 - portable, 417-423
 - rural, 645
 - 60 GHz, 639
 - propagation, 639
- CELP (code excited linear predictive), 491
- Centralized switching systems, 349, 355
- Channel assignment, 257, 279
 - dynamic, 274, 311
 - fixed, 267, 268
 - (See also Fixed channel assignment)
 - non-fixed, 274

- Channel assignment, non-fixed (Cont.):**
 (See also Nonfixed channel assignment)
 to traveling mobile units, 267
Channel coding, 478, 497
Channel combiner, 234
 fixed-tuned, 241
 frequency-agile, 243
 ring, 243
Channel frame, 525
Channel modes, 474
Channel spacing, 75
Channels, 63, 245
 access, 249
CDMA
 primary, 506
 secondary, 506
GSM, 471
NA-TDMA, 500
PHP, 537
 set-up, 248
Channels per cell, number of, 405, 458
Circuit merit (CM), 9
 voice quality, 9
Clearing house concept, 358
CM (communication management), 468
CMAC (control mobile attenuation code), 70
CMAX, 74
Cochannel interference, 189
 directional antenna case, 196
 real-time measurement, 192
 tests, 190-192
 worst case: directional antenna, 198-199
 omnidirectional antenna, 194
Cochannel interference reduction, 189
 designing a system, 217
 diversity receiver, 215
 lowering antenna height, 202
 parasitic elements, 211
 power control, 214
 tilted antenna, 204
 umbrella-pattern effect, 209
Cochannel interference reduction factor, 69, 189
Coders, speech waveform, 449
 hybrid waveform coders-vocoder, 451
 LPC vocoder, 450
 source, 449
 vocoder, time-domain, 450
Coherence bandwidth, 22
Collinear-array case, 162-163
Combiners, antenna, 241
 channel combiner, 241
 frequency-agile combiner, 243
Common Channels, 472
 downlink, 472
 uplink, 472
Componder, 76
Computer generation of point-to-point model, 140
Confidence interval, 116
confidence level, 114
Connectionless services, 628
Continuous-scanning scheme, 332
Continuously variable step delta (CVSD), 451
Control mobile attenuation code (CMAC), 76
Converter (translator), 584
Convolutional codes:
 CDMA, 511
 GSM, 476
 NA-TDMA, 497
Cophase combining, 431
Cophase technique, 317
Coverage of 90% equal-strength contour, 298
Coverage-hole filler, 309, 311
Crosstalk, 233
CSPDN (circuit-switched public data network), 466
CT-2 (cordless phone 2), 539
CT-3 (cordless phone 3), 539
Cumulative distribution function (CDF), 17
CVSD (continuously variable step delta), 452
Cyclic redundancy check (CRC), 496

Data links, 70, 363
Data modem, 423
DCC (digital color code), 74
Decentralized switching systems, 348, 355
DECT, 540
Deemphasis, 76
Delay spread, 22
Demodulation, 439
Demultiplexer, 244
Differential phase-shift-keying (DPSK): modulation system, 489
Diffraction loss, 137
 cautions in obtaining, 138
Digital cellular systems, 464
 cellular, 438
 evaluation of, 460
Digital channel bank, 963
Digital color code (DCC), 74
Digital detection, 430
Digital mobile telephone, 451
Digital speech, 447
Digital systems, 427
 carrier-phase tracking, 431
 evaluation of, 460

- Digital voice, 451
 - (See also Digital speech)
- Dim-and-burst, 494
- Direct call retry, 355
- Direct sequence CDMA, 576
- Direct sequence spreading, 513
- Direct wave path, 23
- Directional antenna, 172, 196-202, 338
- Diversity, 316
 - frequency, 367
 - space, 378
- Diversity receiver, 215, 309, 366
- DPSK (differential phase-shift-keying)
 - modulation system, 389
- DQPSK (differential quadrature phase shift keying), 491
- Dropped call (see Call drops)
- Dropped call rate, 297
- DTX (discontinuous transmission), 469
 - GSM, 469
 - NA-TDMA, 500
- Duct propagation, 130
- Dynamic channel assignment, 274, 311
- D2, 463

- Effective antenna height, 109, 132-133, 146
- Effective radiated power (ERP), 160
- EIR (equipment identity register), 466
- Electronic serial number (ESN), 75, 78
- Elevation angle, 11, 104
- Elevation map, 144
- Emission noise, 24
- Emissions, 495
- Encryption, CDMA, 525, 527
 - GSM, 481
- Energy-per-bit-to-noise-per hertz (E_b/N_0), 453
- Enhancers, 309, 311
- Equivalent aperture, 160
- Erlang B table, 35-42
- ERP (effective radiated power), 160, 241
- Error correction:
 - NA-TDMA, 496
- Error rate, undetected, 446
- ESMR (enhanced SMR), 546
- ESN (electronic serial number), 75, 78
- European cellular systems, 31-32
- Evaluation:
 - of digital cellular systems, 461
 - performance, 381, 386
 - signaling, 388
 - spectrum efficiency, 404
 - system, 381-425

- FACCH (fast associated control channel):
 - GSM, 473
 - FACCH (fast associated control channel)
 - (Cont.):
 - NA-TDMA, 502
 - False-alarm rate, 388
 - FDMA (frequency division multiple access), 463
 - Feedback combining, 432
 - Feedforward combining, 432
 - FER (frame error rate), 602
 - fog (attenuation), 648
 - frequency hopping, 475
 - Field strength, measurement of, and conversion to received power, 158, 160
 - Fifth-wheel vehicle location method, 331
 - First-order statistics of fading, 17
 - Fixed cellular system, 448
 - Fixed-channel assignment, 268
 - adjacent-channel, 268
 - channel sharing and borrowing, 269
 - sectorization, 270
 - underlay-overlay, 271
 - FM (frequency modulation), 407
 - FOCC (forward control channel), 92
 - Foliage loss, 124
 - pine tree, 124
 - Forward control channel (FOCC), 92
 - FPLMTS (future public land mobile telecommunication system), 631
 - Front-to-back ratio, 377
 - Frame bits, 85
 - Free-space formula, 158
 - Frequency-agile combiner, 243
 - Frequency division multiple access (FDMA), 463
 - Frequency management, 257
 - chart, 258
 - new full spectrum (see Full-spectrum management)
 - Frequency modulation (FM), 407
 - narrowbanding in, 414
 - Frequency reuse channels, 56
 - Frequency reuse distance, 57, 65
 - Frequency reuse pattern, 57, 395
 - Frequency shift keying (FSK), 379, 454
 - Frequency spectrum utilization, 260
 - FSK (frequency shift keying), 379, 454
 - Full-spectrum management, 98, 99
 - numbering the channels, 259

- Gain and bandwidth relationship, 163
- Gain and pattern relationship, 161
- Globe-position satellite (GPS), 331
- GMSC (gateway MSC), 467
- GMSK (gaussian minimum-shift keying), 471
- GPS (global position system), 504
- Grade of service, 10

- Granglund combiner, 318
- Ground reflection angle, 105
- Group identification, 75
- GSM (group of special mobile), 463
- GSM channels, 471
- GSM (overview), 485
- GSM handover, 483

- Handing off the call, 358
- Handoff, 26, 65, 74, 263, 386
 - creating a, 290
 - delaying, 288
 - forced, 289
 - initiation of, 286
 - intersystem, 295, 356
 - lost calls due to, 384
 - number of, per cell, 286
 - power-difference, 292
 - probability of, 285
 - queuing of, 290, 311, 356
 - type of, 283
- Handoff blocking, 277
- Handoff or handover (HO), 283
 - CDMA:
 - hard HO, 504, 531
 - soft HO, 504, 531
 - MAHO, 294
 - NA-TDMA, 463
 - GSM, 463
- Hexagonal-shaped cells, 27
- HLR (home location register), 466

- Idle stage, 60
- Ignition noise, 24
- IMPATT diode, 648
- IN (intelligent network), 465
- Inbuilding communications, 573, 594
 - new inbuilding communication system, 595
- Incident angle, 11, 104
- Induced voltage on a monopole or dipole, 159
- Information superhighway, 632
- Intelligent cell, 563
 - intelligent microcell, 564, 568
 - power-delivery, 564
 - processing gain, 575
- Interference, 189, 221
 - caused by portable units, 420
 - cochannel, 189
 - to mobile units, 420
 - noncochannel, 221
 - reduction of, 310
- Interleaving:
 - CDMA, reverse traffic channel, 510
 - forward traffic channel, 520
- Interleaving (Cont.):
 - GSM, 476, 477
 - NA-TDMA, 497
- Intermodulation (IM), 243
- IP (intelligent peripheral), 619
- IR (infrared), 632
- IS-41, 652
- IS-54, 503
- IS-54 (NA-TDMA, ADC), 486
- IS-95, 503
- ISDN (integrated service digital network), 619
 - B-ISDN, 624
 - ISDN-up, 622
- IWF (interworking function), 465

- Japanese cellular system, 29

- Knife-edge diffraction loss, 137, 138

- LAN (local area network), 626
- Large capacity systems, worldwide, 100, 101
- Last 50 meters, 635
- Layer Modeling:
 - CDMA, 504
 - GSM, 468
- LCR (level crossing rate), 18, 395
- Leaky feeder, 319
- Leaky-feeder radio communication, 322
- Leaky waveguide, 319
- LEO (low earth orbit) satellite, 547
- Level-crossing counter, 402
- Level crossing rate (LCR), 18, 395
- Linear predictive code (LPC), 450-451
- Line-of-sight path, 23
- Local mean, 13
- Locating receiver, 332
- Logical channel, 472
- Log-normal fading, 13
- Long code, 505
- Long-distance interference, 254
 - overland path, 254
 - overwater path, 254
- Long-term fading, 13
- Low-density small-market design, 339
- Lowering antenna height, 202, 236
 - in forested area, 203
 - on high spot, 202
 - in valley, 203
- LP (linear predictive code), 450-451, 469

- Macrocell prediction formula, 141
- MAHO (mobile assistance handoff), 141, 294, 483

- MAHO (mobile assistance handoff) (Cont.):**
 GSM, 483
 NA-TDMA, 500
Manchester code, 77
Matched-filter receiver, 427
ME (mobile equipment), 464
Mean opinion score (MOS), 9
MEO (medium-earth-orbit) satellite, 547
Messages transmitted over reverse control channel, 85
Metropolitan statistical areas (MSA), 451
 list of, 48
Microcells, 328, 563, 582
Microwave antennas, 376
 back-to-back coupling, 378
 front-to-back ratio, 377
 horn-reflector, 379
 parabolic dish, 379
 polarization, 378
 side-to-side coupling loss, 378
 space diversity, 378
Microwave links, 9
 available frequencies, 365
 diversity requirement, 366
 high frequencies, 376
 4 GHz, 365
 6 GHz, 365
 11 GHz - 23 GHz, 365-366
Midamble, 476
Millimeter-wave link, 628
MIN (mobile identification number), 74,
 78
MM (mobility management), 466, 480
Mobile antenna height-gain formula, 106
Mobile antennas, 180
 glass-mounted, 183
 high-gain, 183
 roof-mounted, 181
 space-diversity: horizontally oriented,
 184
 vertically oriented, 186
Mobile cellular system, portable cellular system, comparison of, 421
Mobile identification number (MIN), 74,
 78
Mobile originated call, 26
Mobile path-loss formula:
 general nonobstructive, 118
 theoretical, 115
Mobile satellite communications, 447
 LEO (low-earth-orbit) satellite, 547
 MEO (medium-earth-orbit) satellite,
 547
 stationary satellite, 547
Mobile telephone switching office (MTSO), 8
Mobile-to-mobile propagation, 118
Modulation:
 AMPS, 76
Modulation (Cont.):
 CDMA, 503, 518
 forward CDMA channel, 518
 reverse CDMA channel, 503
 GSM, 471
 NA-TDMA, 491
Modulation schemes, 435
 analogy, 428
 GMSK, 429
 modified GSK, 437
 MSK, 429
 QPSK, 435
Modulation timing (ADC), 490
MOS (mean opinion score), 9
MS (mobile station), 464
MSA (metropolitan statistical areas), 241
MSC (mobile switching center), 464
MTA (major trading area), 543
MTP (message transfer part), 469, 621
MTSO (mobile telephone switching office), 8, 359
 cell-site trunks, 359
 connection to a cell site, 359
 connections, 359
 type 1, 359
 type 2, 359
 traffic concentrator, 360
Multipath fading (see Rayleigh fading)
Multiple-access scheme, 474

Narrowbanding in FM, 414
Narrowbeam concept, 334
NA-TDMA (ADC, IS-54), 486
Near-field propagation, 128
New frequency management, 98, 99
(See also Additional spectrum management)
NM (network management), 485
NMT network, 31
Noise, 23
 amplifier, 24
 emission, 24
 ignition, 24
 thermal, 23
Noise figure F, 25
Noise level, 23
 average, 398, 399
Noise power, available, 24
Noncellular System, 544
 CDPD (cellular digital packet data),
 544
 MIRS (mobile integrated radio system),
 546
Noncochannel interference, 221
 adjacent channel, 225
 cross talk, 233
 long-distance, 254

- Noncochannel interference (Cont.):**
 near-end-far-end, 226
 in cells of two systems, 227
 in one cell, 226
 near-end mobile unit, 233
 neighboring channel, 225
 next-channel, 225
 nonlinear amplifier, 231
 between systems, 247
 in adjacent cities, 249
 in one city, 247
 TV, 250
- Noncochannel interference reduction, 236**
 antenna height decrease, 236
 antenna pattern, 237
 avoidance of near-end-far-end, 229
 lower antenna height, 236
 power control, 236
 transmitting and receiving antennas at cell site, 240
- Nonfixed channel assignment, 274**
 borrowing, 274
 dynamic, 274
 forcible-borrowing, 274
 hybrid, 274
- Nonlinear amplification, 231**
- Non-return-to-zero binary data, 77**
- Nordic cellular system, 31**
- NSS (network and switching subsystem), 465**
- NTT (Nippon Telegraph and Telephone Corporation) system, 29**
- Null-free patterns, 167**
- Null traffic data, 505**
- Number of channels per cell, 405, 408**
- OAAM (operation, administration and maintenance), 468**
- Objective test to measure voice quality, 221**
- Obstructive path, 23**
- OMAP (operation, maintenance and administration part), 621**
- Omnidirectional antenna, 62, 194, 327**
- Optical-wave link, 628**
- OSI (open system interconnection), 465, 468**
- OSI modeling, 468**
- OSS (operation subsystem), 464**
- Paging channel, 74**
 CDMA, 503
 GSM, 471
 NA-TDMA, 463
- Paging channel selection, 80**
- Parasitic elements, 211**
- Parity check bits, 392**
- Passive reflector, 313**
- Path loss, 11**
 building penetration, 407
 general formula, 118
 theoretical formula, 115
 (See also Propagation)
- Path-loss curve, standard deviation along, 113**
- Patterns:**
 antenna element, 161
 difference, 167
 null-free, 167
 sum, 165
- PCM (pulse-code modulation), 462**
- PCN (personal communications network), 543**
 narrowband, 543
 wideband, 543
- PCS application (inbuilding system), 598**
- PDC (personal digital cellular), 541**
- Performance evaluation, 381, 386**
- Phase difference between direct path and ground reflected path, 110**
- Phase equalization circuits, 432**
- Phase-locked loop, 431**
- PHS (personal handy phone system), 535**
- Pilot channel, 506**
- Pilot sets, 531**
- PIN (personal identification number), 501**
- PLMN (public land mobile network), 480**
- Point-to-point model, 106**
 general formula, 140
- Polarization, 378**
- Portable cell site, 333**
- Portable cellular systems, 417**
 building penetration, 417-418
 coverage charts, 421
 design concept, 422
- Portable units, 417**
- Power, required, 407**
- Power control, 214, 236, 307, 503**
 closed-loop, 510
 open loop, 510
- Power level, 75**
 CDMA, 503
 NA-TDMA, 503
- Prediction model, 140, 141**
 point-to-point, 141
 macrocell, 141
 microcell, 141
- Premphasis, 76**
- Processing gain, 577, 579**
- Processor traffic, 448**
- Propagation:**
 bending, 369, 374
 building height effect, 49, 409
 building penetration, 417
 computer generation, 142
 duct, 130

- Propagation (Cont.):**
 foliage loss, 124
 hyper reflectivity, 374
 long-distance, 128
 merit of point-to-point model, 141
 mobil-to-mobile, 149
 near-field, 128
 near-in, 126
 non-obstructive, 131
 obstructive, 137
 over water, 119
 fixed station, 120
 land-to-mobile, 123
 rain effect, 366
 ray-bending phenomenon, 369
 60 GHz, 436
 transfer function of propagation channel, 149
 trapping, 130
 troposphere, 129, 370
PSPDN (packet-switched public data network), 466
Pulse-code modulation (PCM), 452
- Queuing, 311, 356**
Queuing feature, 356
- Radio capacity, 405, 565**
Radio channels, 98-99
Radius of scatterer region, 15
Rainfall (attenuation), 630
Rayleigh fading, 13
Rayleigh fading environment, 405, 411
RECC (reverse control channel), 86
Receiver, 309
 diversity, 309
 low-noise, 309
Receiver sensitivity, 402
Reflection point, 105
Reflector, passive, 313
Refractive index, 360
Registration, 263, 529
Registration, autonomous, 75, 263
Reliability (see System reliability)
Repeater, 378
 (See also Enhancers)
Retransmission, selective, 446
Reverse control channel (RECC), 86
Reverse voice channel, 86
Roamer, 75, 357
Roof-top mounted antennas, 181, 315
RPE (regular pulse excitation), 469
RR (radio resource management), 478
RSA (rural service area), 241
Rural service areas (RSA), 450
 list of, 48
- SACCH (slow associated control channel):**
 GSM, 473
 NA-TDMA, 503
Sampling average, 396
SAT (see Supervisory audiotone)
Scan access channels, 81
Scanning receiver, 585
 continuous-scanning scheme, 332
 scan-under-request scheme, 333
SCM (station class mark), 499
SCP (service control point), 617
SDCCH (stand-alone dedicated control channel, 473
 SSM (supplementary services management), 484
 STP (signaling transfer point), 467
Second-order statistics of fading, 17
Security management, 482
Seize reverse control channel, 81
Self-location scheme in paging, 263
Service quality, 10
Setup channels, 73
Shared secret data (SSD), 506
Short message service, 469
Short-term fading, 13
SID (silence detection), 469
SID (system identification), 75, 79, 499
Signal-strength conversion, 401
Signaling channels, 472
Signaling format, 85
Signaling tone, 74, 79
SIM (subscriber identity module), 464, 482
SINAD, 222
Single sideband (SSB), 3, 407
Six-sector case, 200
Small cells, 328
SMR (special mobile radio), 546
Soft handoff, 531
Sonet, 623
Space diversity, 378
Space-diversity antennas, 175, 184, 186
Space-division switching, 344
Spatial time correlation, 152
SPC (store program control), 606
Speech, 469
Spectrum efficiency, 3, 416
Spectrum utilization, 2
Speech coding, 447, 491
 CDMA, 463, 503
 GSM, 463
 NA-TDMA, 463
 transmission rates in: commentary
 quality, 447
 communications quality, 447
 synthetic quality, 448
 toll quality, 447
Spread spectrum, 448

- Spreading:
 - direct sequence, 513
 - quadrature, 515
 - orthogonal, 521
- SSB (single sideband), 407
- SS6, 618
- SS7, 618
- Standard condition for area-to-area prediction, 106
- Standard deviation along a path loss curve, 113
- Standing wave ratio (SWR), 17
- Stationary satellite, 547
- STP (signaling transport point), 620
- Subjective test to measure voice quality, 221
- Sum-and-difference pattern, 164
- Sum patterns, synthesis of, 165
- Supervisory audiotone (SAT), 75, 79, 244
 - interference conditions, 384
 - lost calls due to, 384
- Switching:
 - basic, 343
 - blocking probability, 345
 - call congestion, 347
 - elements of, 353
 - multistage, 345
 - space-division, 344
 - system congestion, 346
 - time congestion and, 346
 - time-division, 344
- Switching equipment, 70
 - analog, 349
 - modification of, 350
 - cellular analog, 349
 - cellular digital, 352
 - digital, 343
 - dimension of, 346
- Switching systems:
 - centralized, 349, 355
 - decentralized, 348, 355
 - small, 360
 - ultimate system capacity, 347
- SWR (standing wave ratio), 17
- Synchronization bit, 85
- System capacity, ultimate, 347
 - due to control, 347
 - due to traffic load, 347
- System congestion, 346
- System enhancement, 360
- System identification (SID), 75, 79
- System parameters, 307
- System reliability, 371
 - equipment reliability, 371
 - path reliability, 372
 - power system reliability, 376
- 39 dBu boundary, 240
- TACS (total access communications system), 30
- TADD, 532
- TCAP (transaction capabilities application port), 621
- TCH (traffic channel), 472
- T-carriers, 9
- TDD (time division duplexing), 534
- TDMA (time division multiple access), 449, 474
 - TDMA structure (ADC), 488
 - TDrop, 532
 - Terrain elevation contour, 145
 - Terrain elevation data, 142
 - Thermal noise, 23
 - Three-sector case, 196
 - Threshold level, lowering, 299
 - Tilting antenna, 205
 - caution in, 209
 - notch appearing, 208
 - Time alignment (NA-TDMA), 494
 - Time slots (different types), 475
 - Time-division switching, 344
 - Traffic, 279
 - Traffic capacity, 311
 - Traffic channel:
 - CDMA:
 - forward, 510, 518, 519
 - reverse, 516
 - GSM, 471
 - NA-TDMA, 500
 - Traffic density, 24
 - Traffic handling features, 355
 - direct-call retry, 355
 - hybrid systems-high sites and low sites, 356
 - underlay-overlay, 355
 - Traffic load on setup channel, 265
 - Translator (converter), 572
 - Transmission modes, 478
 - Transmissions, expected number of, 442
 - Transmissions efficiency, 445
 - Trapping propagation, 130
 - TRAU (transcoder/rate adaption unit), 464
 - Triangulation, 332
 - Tropospheric reflection, 130
 - Tropospheric refraction, 130
 - Tropospheric wave propagation, 129
 - Trunking efficiency, 6
 - TV interference, 250
 - of cellular mobile receivers by TV transmitters, 253
 - to TV receivers from cellular mobile transmitters, 250
- Underlay-overlay, 267, 339
- 32 dBu boundary, 240

United Kingdom cellular system, 30

VAD (voice activity device), 469

Vehicle-locating methods, 331

angular arrival, 332

fifth wheel, 331

globe-position satellite (GPS), 331

gyroscope, 331

response-time arrival, 332

triangulation, 332

VLR (visitor location register), 467

VMAC, 76

Voice channels, 73

selection of, 268, 267

Voice privacy, 528

Voice quality, 9, 221, 386

Voice quality (*Cont.*):

SINAD, 222

subjective test versus objective test, 221

Voltage-to-power conversion, 160

VSWR (voltage standing-wave ratio), 243

VSELP (vector-sum excited linear predictive), 491

Wireless information superhighway, 632

Word-error rate (WER), 389, 390, 424

fast fading case, 391

slow fading case, 391

ABOUT THE AUTHOR

William C. Y. Lee is Vice President of Technology at PacTel Cellular, Inc. He was elected a Fellow of the Institute of Electrical and Electronics Engineers for his distinguished work in mobile communications, and frequently leads professional seminars on the subject, both in the United States and abroad. Dr. Lee has written more than 170 articles for professional journals, three textbooks, and is the author of *Mobile Communications Engineering*, also available from McGraw-Hill.