
Index

A

AC, 126
 Access time, 463
 Accumulator, 126
 Accumulator register, 128–30
 design of, 164–65
 Addend, 338
 Adder, 103–4
 Adder and logic circuit, 130, 166
 Adder-subtractor, 104–5
 Addition algorithms:
 decimal numbers, 365–68, 371
 floating-point, 358–60
 signed-magnitude, 335–38
 signed-2's complement, 79, 338–40
 Add microoperation, 102–4
 Add-overflow, 336
 Address, 60, 131
 Address bus, 417–19
 Address field, 226
 Addressing modes, 260
 autoincrement, 262
 base register, 264
 direct, 126–27, 263
 immediate, 126, 262
 implied, 261
 indexed, 263–64
 indirect, 126–27, 263
 register, 262
 register indirect, 262
 relative, 263
 Address mapping, 472
 Address register, 128–30
 Address sequencing, 216
 Address space, 470
 Address symbol table, 183
 Adjacent squares, 12
 Algorithm, 334
 Alphanumeric code, 73, 86, 383
 ALU, 116–17, 241–45
 AND, 4
 AND gate, 5

AND microoperation, 110–11
 special symbol, 109
 AR (*see* Address register)
 Arbitration, 500
 Arbitration algorithms, 505
 Arbitration switch, 513
 Architecture, 3
 Arithmetic algorithm, 334
 Arithmetic circuit, 106–8
 Arithmetic instructions, 269–70
 Arithmetic logic unit, 116, 244–45
 Arithmetic microoperations, 102–3
 Arithmetic pipeline, 307–10
 Arithmetic processor, 333
 Arithmetic shift, 114–15, 272, 346
 overflow, 115
 Array multiplier, 346–48
 Array processor, 326
 attached, 326–27
 SIMD, 327–28
 ASCII, 74–75, 184, 383–85
 Assembler, 182, 185–90
 Assembly language, 179–81
 Associative memory, 456
 hardware organization, 457–60
 write-back, 469
 write-through, 469
 Associative mapping, 464
 Asynchronous bus, 501
 Asynchronous communication, 398–400
 Asynchronous transfer, 391, 396
 Attached array processor, 326–27
 Autodecrement, 262
 Autoincrement, 262
 Auxiliary memory, 445, 452–56

B

Base of a number, 68
 Base register, 264
 Basic computer, 123
 common bus, 129–31

- Basic computer (*cont.*)
 - control, 135-39
 - design of, 157-67
 - flowchart, 158
 - input-output, 150-53
 - instruction cycle, 139, 142, 158
 - instructions, 132-34, 174-75
 - interrupt, 153-56
 - phases, 139
 - registers, 128, 157
 - tabular summary, 159
 - Baud rate, 398
 - BCD, 72-73, 81-82
 - BCD adder, 365-68
 - BCD subtractor, 368-69
 - Berkeley RISC I, 288-91
 - Biased exponent, 356
 - Bidirectional shift register, 53-56
 - Binary, 1
 - Binary adder, 103-4
 - Binary-coded decimal, 73, 85
 - Binary codes, 72, 84
 - alphanumeric, 73
 - ASCII, 74-75
 - BCD, 72-73
 - error detection, 87
 - excess-3, 85-86
 - Gray, 84
 - Binary counter, 56-58
 - design of, 32-36
 - with parallel load, 58-59
 - Binary incrementer, 105-6
 - Binary n -cube, 498
 - Binary numbers, 2, 68
 - Binary parallel adder, 103-45
 - Binary point, 77
 - Binary signal, 4
 - Binary tree, 497
 - Binary variable, 7, 213
 - Bit, 1
 - Bit-clear, 270
 - Bit complement, 270
 - Bit manipulation instructions, 270-72
 - Bit-oriented protocol, 437-39
 - Bit-set, 271
 - Block, 472
 - Block diagram, 18
 - Block transfer, 431
 - Boolean algebra, 7-11
 - Boolean expression, 8
 - Boolean function, 7
 - Booth algorithm, 343-46
 - Bootstrap loader, 448
 - Branch, 147, 275
 - Branch conditions, 276
 - Branch instructions, 273-76, 314-15
 - Branch logic, 217
 - Branch target buffer, 315
 - Buffer gate, 5, 100
 - Burst transfer, 416
 - Bus, 97-98, 500
 - of basic computer, 129-31
 - construction of, 98-101
 - input-output, 386
 - memory, 453
 - Bus arbitration, 502-6
 - Bus grant, 416
 - Bus organization, 242-44
 - Bus request, 416
 - Bus selection, 99
 - Bus transfer, 99
 - Byte, 60
- ## C
- Cache coherence, 509-12
 - Cache memory, 446, 462-69
 - Call subroutine, 200
 - CAM, 456
 - CAR (*see* Control address register)
 - Carry, 19, 76
 - Carry status bit, 274
 - Central processing unit, 241
 - Channel, 423
 - Character code, 73
 - Character manipulation, 204
 - Character-oriented protocol, 432
 - Characteristic table, 23-25
 - Chip, 41, 449
 - Chip select, 449
 - CISC, 282
 - Circular shift, 114
 - Clear, 23, 113
 - Clock, 22, 26, 96
 - Clock cycle, 137, 305
 - Clocked sequential circuit, 22
 - CMOS, 43
 - Combinational circuit, 18
 - analysis, 19
 - design, 19
 - Combinational circuit shifter, 116
 - Command, 387, 421
 - Comment field, 179
 - Common bus, 97-98, 129-31, 242-44
 - Communication control characters, 432
 - Compiler, 190
 - Compiler support, 316
 - Complement, 10, 74-76
 - subtraction with, 76
 - Complementer, 336-37
 - Complex instruction set computer, 282-84
 - Computer architecture, 3
 - Computer arithmetic, 333
 - Computer design, 3, 157-67
 - Computer hardware, 1
 - Computer instruction cycle, 139
 - Computer instructions, 132-34, 175

Computer network, 489
 Computer organization, 3
 Computer registers, 128
 Computer software, 2, 173
 Condition code, 274
 Conditional branch, 217, 275-76
 Content addressable memory, 456
 Control address register, 215, 217
 Control command, 387
 Control design, 160-64, 231-32
 Control function, 96
 Control logic gates, 160
 Control memory, 213-14, 229
 Control signal, 136-38
 Control unit, 135-39, 231
 Control word, 213, 243-45
 Counter, 56-58
 design of, 32-36
 CPU, 3, 241
 CRC, 431
 Critical section, 508
 Crossbar switch, 494-96
 Cycle stealing, 416
 Cyclic redundancy check, 431

D

Daisy-chain, 408, 502-3
 Data bus, 417-19
 Data communication, 429
 Data communication protocol, 431
 bit-oriented, 437-39
 character-oriented, 432-33
 example, 433-36
 message format, 433, 437
 Data dependency, 313-14
 Data link, 431
 Data manipulation instructions, 268-72
 Data register, 128-30
 Data representation, 67
 Data selector, 49
 Data set, 430
 Data stream, 301
 Data transfer instructions, 267-68
 Data transparency, 436
 Data types, 67, 269
 Decimal adder, 365-68
 Decimal arithmetic, 369-76
 addition and subtraction, 371
 division, 374-76
 multiplication, 371-73
 Decimal arithmetic unit, 363-69
 Decimal codes, 85
 Decimal numbers, 68, 81
 Decimal representation, 81
 Decimal subtraction, 368-69
 Decode phase, 139, 226
 Decoder, 43

Decrement, 108
 Delayed branch, 315, 318-19
 Delayed load, 314, 317-18
 DeMorgan theorem, 8-10
 Descriptor, 482
 Design of basic computer, 157-67
 Device, 382
 D flip-flop, 23
 Digital, 1
 Digital computer, 1
 Digital integrated circuits, 41
 Digital logic families, 42
 Digital signal, 4
 Digital system, 1
 Direct address, 126-27, 263
 Direct mapping, 465
 Direct memory access, 415-20
 controller, 416-18
 transfer, 418-20
 Disk, 383, 454
 Distributed memory, 491
 Distributed switch, 513
 Divide overflow, 351
 Dividend, 349
 Dividend alignment, 362
 Division algorithms:
 comparison method, 353
 decimal numbers, 374-76
 floating-point, 362-63
 non-restoring, 353-54
 restoring method, 353
 signed-magnitude, 349-53
 Divisor, 349
 DLE character, 436
 DMA (*see* Direct memory access)
 Don't-care conditions, 16
 Double-precision, 196
 DR (*see* Data register)
 Drum, 454
 Dual-bus, 492-93
 Dynamic arbitration, 505
 Dynamic input, 22-23
 Dynamic microprogramming, 214
 Dynamic relocation, 476

E

EBCDIC, 87
 ECL, 43
 Edge triggered flip-flop, 25
 EEPROM, 63
 Effective address, 126, 262
 Emitter-coupled logic, 43
 Enable input, 44
 Encoder, 47
 End carry, 76
 EPROM, 63
 Equivalence, 5

Error detection code, 87
 Error diagnostics, 188
 Excess-3 code, 85-86
 Excitation table, 27, 33
 Exclusive-NOR, 5
 Exclusive-OR, 6, 111
 Execute phase, 139, 228
 Exponent, 83, 354
 External interrupt, 281

F

FA (*see* Full-adder)
 Fetch phase, 139-41, 156, 226
 FIFO, 400, 476
 FIFO buffer, 400-2, 505
 First-in first-out, 400-2
 Fixed-point, 77
 binary representation, 79-80
 decimal representation, 81-82
 Flag, 152, 437
 Flag bits, 274
 Flip-flop, 22-28
 asynchronous clear, 26
 edge-triggered, 25
 excitation table, 27
 IC, 26
 input function, 28
 master-slave, 26
 types of, 22-25
 Floating-point, 83, 354-57
 arithmetic operations, 358-63
 normalization, 83, 355
 Floating-point pipeline, 308-10
 Floppy disk, 455
 Flops, 325
 Flowchart for basic computer, 158
 Fortran, 178
 Full-adder, 20-22, 104
 Full-duplex, 431

G

Gates, 4-6
 General register organization, 242-47
 Graphic symbols, 23
 Gray code, 84

H

Half-adder, 19
 Half-duplex, 431
 Handshaking, 391, 393-96
 Hardware, 2, 173
 Hardware algorithm, 334
 Hardware interlock, 312
 Hardware lock, 508

Hardwired control, 136, 216
 HDLC, 437
 Hexadecimal code, 134, 177
 Hexadecimal numbers, 68-70
 binary coded, 71
 conversion to binary, 70
 High-impedance, 100
 Hit ratio, 463
 Hold time, 26
 Hypercube, 498-500

I

IBM channel, 423-26
 IC (*see* Integrated circuit)
 Immediate mode, 126, 262
 Implied mode, 261
 Increment, 58, 103, 108
 Incrementer, 105-6
 Index addressing, 263-64
 Indirect address, 126-27, 132, 263
 Infix notation, 252
 Inner product, 322
 Input carry, 106
 Input equation, 28
 Input flag, 152
 Input logic, 233-35
 Input-output, 150-53, 381
 bus, 386, 421
 devices, 381-83
 instructions, 152
 interface, 385-87, 389-91
 programming, 203
 transfer, 391-98
 Input-output processor, 420-22
 Instruction code, 123, 132
 Instruction cycle, 139, 310-11
 Instruction format, 255, 322
 Instruction register, 128
 Instruction pipeline, 310-15
 Instruction set completeness, 134-35
 Instruction stream, 301
 Instructions, 133, 175
 Integrated circuit, 41-43
 Intel-8089 IOP, 427
 Interchange switch, 496
 Interconnection of processors, 491-500
 Interface, 385, 389
 Interleaved memory, 324
 Internal interrupt, 281
 Interprocessor arbitration, 500
 Interprocessor communication, 506
 Interprocessor synchronization, 507
 Interregister transfer, 95
 Interrupt, 153-56, 281, 407-12
 priority, 407
 types of, 281-82
 vectored, 406

Interrupt acknowledge, 410
 Interrupt cycle, 153-56, 412-13
 Interrupt initiated I/O, 46
 Interrupt program, 205-8
 Interrupt register, 411
 Interrupt request, 417
 Inverter gate, 5
 IR (*see* Instruction register)
 I/O, 381
 I/O bus, 421
 I/O instructions, 152
 I/O interface, 385-87
 I/O port, 389
 I/O software, 406, 413
 IOP (*see* Input-output processor)
 Isolated I/O, 388

J

JK flip-flop, 24
 Jump, 225, 273

K

Karnaugh map, 11
 Keyboard, 382

L

Label, 179, 225
 Large-scale integration, 42
 Last-in first-out, 247
 LD (*see* Load control)
 Least recently used, 476
 LIFO, 247
 Load control, 52, 129
 Load input, 129-31
 Local bus, 492-93
 Locality of reference, 462
 Location counter, 185
 Lock mechanism, 508
 Logic circuit, 111
 Logic circuit families, 42
 Logic diagram, 7
 Logic gates, 4
 Logic microoperations, 108-10
 hardware implementation, 111
 list of, 109-10
 Logic operations, 197
 Logical address, 477
 Logical instructions, 270-72
 Logical shift, 114, 272
 Loosely coupled multiprocessors, 491
 LRC, 431
 LRU, 476, 505
 LSI, 42

M

M (*see* Memory word)
 Machine language, 174-75
 Magnetic disk, 383, 454
 Magnetic drum, 383
 Magnetic tape, 383, 455
 Magnitude, 335
 Magnitude comparator, 336
 Main memory, 445, 448
 Mantissa, 83, 354
 Map simplification, 11-18
 Mapping, 216, 219, 463
 Mask operation, 113
 Mask register, 411
 Master-slave flip-flop, 26
 Match logic, 459
 Matrix multiplication, 322
 Medium-scale integration, 42
 Memory:
 access time, 463
 associative, 456-62
 auxiliary, 452-56
 cache, 462-69
 chip, 449
 content addressable, 456
 FIFO, 400
 IC, 41, 449
 random access, 60, 448
 read only, 61, 450
 virtual, 469
 Memory address, 60, 131
 Memory address map, 450-52
 Memory array, 324
 Memory bus, 387, 453
 Memory cycle, 138
 Memory hierarchy, 445
 Memory interleaving, 324
 Memory management, 476-79
 Memory-mapped I/O, 388-89
 Memory module, 494
 Memory organization, 445
 Memory page table, 473, 478
 Memory protection, 482
 Memory read, 61, 101
 Memory reference instructions, 145-50
 Memory space, 470
 Memory stack, 249-51
 Memory transfer, 101-2
 Memory word, 58, 101
 Memory write, 60-61, 101-2
 Message format, 433
 Message-passing, 491
 Message routing, 499
 Metal-oxide semiconductor, 43
 Microcomputer, 500
 Microinstruction, 214
 binary form, 229-30
 formats, 222-24
 symbolic form, 225-28

Microoperation, 93, 102, 223, 246
 arithmetic, 102-3
 logic, 108-10
 read, 101
 register transfer, 102
 shift, 114-15
 write, 102
 Microprocessor, 490
 Microprogram, 214
 binary, 229-30
 control, 231-32
 example, 220-30
 sequencer, 232-35
 symbolic, 225-28
 Microprogrammed control unit, 214
 Minterm, 11
 Minuend, 338
 MIMD, 301, 489
 Mode field, 261, 265
 Modem, 430
 Modes of transfer, 402-3
 Monitor, 382
 MOS, 43
 Move instruction, 256
 MSI, 42
 Multiple functional unit, 300; 306
 Multiplexer, 48-50, 98
 Multiplicand, 340
 Multiplication algorithms:
 Booth algorithm, 343-46
 decimal numbers, 371-73
 floating-point, 360-62
 signed-magnitude, 341-43
 signed-2's complement, 343-46
 software implementation, 195
 Multiplication program, 193-96
 Multiplier, 340
 Multiport memory, 493
 Multiprocessor, 489
 arbitration, 500-6
 communication, 506
 interconnection, 491-500
 synchronization, 507-9
 Multiprogramming, 447
 Multistage switching network, 496-98
 Mutual exclusion, 508
 MUX (see Multiplexer)

N

NAND gate, 5, 9, 16
 Next state, 23, 30
 NOR gate, 5, 9, 16
 Normalization, 83, 355
 Number base conversion, 68-71
 Number system, 68

O

Object program, 183
 Octal numbers, 68-72
 binary coded, 70
 conversion to binary, 70
 Odd function, 6, 88
 Omega network, 497-98
 One-address instruction, 259
 On-line, 382
 Opcode, 125
 Operating system, 447, 483, 506
 Operation code, 124, 255
 ORG, 180, 226
 OR gate, 5-6
 OR microoperation, 110-11
 special symbol, 109
 Output flag, 152
 Overflow, 80-81, 115
 Overflow status bit, 274
 Overlap register window, 285-88

P

Packet, 491
 Page, 472
 Page fault, 475
 Page frame, 472
 Page replacement, 475
 Page table, 474
 Parallel adder, 336-37
 Parallel arbitration logic, 503-5
 Parallel load, 54
 Parallel processing, 299
 Parallel transfer, 51
 Parameter linkage, 200
 Parity bit, 87
 Parity checker, 87-89
 Parity generator, 87-89
 Partial product, 341, 343
 Partial remainder, 349
 PC (see Program counter)
 Peripheral, 382
 Pipeline, 302-7
 arithmetic, 307-10
 in RISC, 315-19
 instruction, 310-15
 Pipeline conflicts, 313
 Pipeline processing, 299
 Pointer, 192
 Polish notation, 252
 Polling, 407, 505
 Pop stack, 249
 Port, 389
 Present state, 23, 30
 Printer, 382
 Priority encoder, 411-12

- Priority interrupt, 407-12
 - daisy-chaining, 408-9
 - parallel, 409-11
 - software routines, 413-15
 - Priority logic, 410
 - Product, 340
 - Product of sums, 14
 - Program, 2, 173
 - Program control instructions, 273-74
 - Program counter, 128-30
 - Program interrupt, 153-56, 205, 279
 - Program loop, 190
 - Program status word, 280
 - Programmed I/O, 402-6
 - Programming languages, 176
 - PROM, 63
 - Protection, 482
 - Protocol, 431
 - Pseudo-instruction, 178-80
 - Push stack, 247-49
 - PSW, 280
- R**
- Radix, 68
 - RAM, 60, 448
 - Random-access memory, 60-61, 448-50
 - Read, 60-61, 101
 - Read microoperation, 101
 - Read only memory, 61-63, 448
 - programming of, 62-63
 - truth table, 62
 - types of, 62-63
 - Reduced instruction set computer, 282-85
 - characteristics, 284-85
 - instructions, 259-60, 288-89
 - pipeline, 315-19
 - Register, 50, 95
 - Register address, 255
 - Register indirect mode, 262
 - Register load, 50
 - Register mode, 262
 - Register with parallel load, 51
 - Register-reference instructions, 143-44
 - Register stack, 247-49
 - Register transfer, 95
 - Register transfer language, 94
 - basic symbols, 97
 - Register transfer statements, 95
 - arithmetic, 102-3
 - conditional control, 96
 - logic, 108-10
 - shift, 114
 - Registers of basic computer, 128, 157
 - Relative addressing, 263
 - Remainder, 349-50
 - Replacement algorithms, 475-76
 - Resource conflict, 313
 - Return address, 148
 - Return from subroutine, 278
 - Reverse Polish notation, 251-54
 - arithmetic expressions, 253-54
 - RISC, 282-85
 - instructions, 259-60, 288-91
 - pipeline, 315-19
 - ROM, 61, 214, 230, 450
 - Rotating daisy-chain, 505
 - Routine, 216
 - RPN, 252
- S**
- Schottky TTL, 42
 - SDLC, 437
 - Sector, 455
 - Segment, 304, 477
 - Segment descriptor, 482
 - Selection inputs, 48
 - Selective-clear, 112
 - Selective-complement, 112
 - Selective-set, 112
 - Self-complementing code, 86
 - Semaphore, 508
 - Sequence counter, 341
 - Sequencer, 215, 232-35
 - Sequential circuit, 28
 - design of, 32-36
 - Serial communication, 429
 - Serial communication interface, 151
 - Serial input, 53
 - Service program, 414
 - Service routine, 207
 - Set, 23
 - Set-associative mapping, 467
 - Setup time, 26
 - Shared memory system, 491-92
 - Shifter, 115-16
 - Shift instructions, 371-72
 - Shift microoperations, 114
 - hardware implementation, 115-16
 - Shift operations, 197
 - Shift register, 53
 - Signal, 4
 - Sign status bit, 274
 - Signed-magnitude, 78
 - Signed-2's complement, 78
 - overflow, 86
 - Signed numbers, 78
 - SIMD, 301, 327
 - Simplex, 431
 - Single-cycle execution, 316
 - SISD, 301
 - Small-scale integration, 41
 - Snoopy cach controller, 512
 - Software, 2, 173, 406, 413
 - Software interrupt, 281-82

- Source program, 183
 - SP (see Stack pointer)
 - Space-time diagram, 304-5
 - Speedup ratio, 305-6
 - SR flip-flop, 22
 - SSI, 41
 - Stack, 247
 - Stack instructions, 259
 - Stack limit, 251
 - Stack operations, 254
 - Stack organization, 247-49
 - Stack pointer, 247
 - Start bit, 396
 - State diagram, 31-32
 - State table, 30-31
 - Status bits, 217, 274
 - Status command, 387
 - Status register, 404
 - Stop bit, 397
 - Store, 147
 - Stored program organization, 125
 - Strobe control, 391
 - Subroutine, 198, 278-79
 - Subroutine call, 148, 200, 278
 - Subroutine parameters, 200
 - Subroutine program, 199
 - Subroutine register, 220
 - Subroutine return, 200, 278
 - Subtraction algorithms:
 - decimal numbers, 368-69, 371
 - floating-point, 358-60
 - signed-magnitude, 335-38
 - signed-2's complement, 89, 338-40
 - unsigned numbers, 76
 - Subtract microoperation, 102-5
 - Subtractor, 104-5
 - Subtrahend, 338
 - Sum of minterms, 11
 - Sum of products, 14
 - Supercomputer, 325
 - Supervisor mode, 280
 - Symbol table, 183
 - Symbolic address, 179
 - Symbolic microprogram, 227
 - Symbolic program, 175, 184
 - SYN character, 432
 - Synchronization, 507
 - Synchronous bus, 501
 - Synchronous clear, 58
 - Synchronous transfer, 396
 - Synchronous transmission, 430
 - System bus, 493, 500-2
- T**
- Table-lookup, 187
 - Tag field, 465
 - Tape, 383, 455
 - Task, 304
 - Test and set, 508
 - T flip-flop, 24
 - Three-address instruction, 258
 - Three-state buffer, 100
 - Three-state bus, 100-1
 - Throughput, 299
 - Tightly coupled multiprocessor, 491
 - Time shared bus, 491-93
 - Time slice, 505
 - Timeout, 396
 - Timing and control, 135
 - Timing diagram, 26, 391
 - Timing signal, 136-38
 - TLB, 479
 - Track, 455
 - Transistor-transistor logic, 42-43
 - Translation look-aside buffer, 479
 - Trap, 281
 - Truth table, 4, 7
 - TTL, 42
 - Two-address instruction, 258
- U**
- UART, 398
 - Underflow, 356
 - Unsigned numbers, 76
 - subtraction of, 76-77
- V**
- Valid bit, 469
 - Vector address, 408
 - Vector operations, 321
 - Vector processing, 319
 - Vectored interrupt, 406
 - Video monitor, 382
 - Virtual address, 470
 - Virtual memory, 469
 - VLSI, 42, 490
- W**
- Weighted code, 86
 - Word, 58
 - Word count register, 417
 - Write, 60-61, 101
 - Write microoperation, 102
 - Write-back, 469
 - Write-through, 469
- X**
- XOR (see Exclusive-OR)

Z

- Zero-address instruction, 259
- Zero detection, 275
- Zero insertion, 437
- Zero status bit, 274

